

[print out](#)

Patent Number 367523

Title Method for evacuating and sealing field emission displays

Publication Date 1999/08/21

Certification\_Number 105760

Application Date 1986/11/07

Application No. 085113617

IPC H01J-009/39;H01J-009/40

Inventor DYNKA, DANNYUS;  
CATHEY, DAVID A. JR.US;  
KINSMAN, LARRY D.US

Applicant MICRON TECHNOLOGY, INC.US

Priority Number 1995/09/29 US19950538498

**Abstract** A method for evacuating and sealing a field emission display package is provided. The method includes forming a cover plate, a backplate, and a peripheral seal therebetween. The backplate is formed as a sub-assembly which includes a seal ring and a getter material. The seal ring includes compressible protrusions for initially separating the cover plate from the seal ring to provide evacuation openings. During a sealing and evacuation process the packages are placed in the reaction chamber of a furnace. The pressure in the reaction chamber is then reduced and the temperature is increased in a staged sequence. During the evacuating and sealing process the evacuation openings formed by the compressible protrusions provide a flow path for evacuation. As the sealing and evacuation process continues, the compressible protrusions and seal ring flow and commingle to form the peripheral seal. At the same time the getter material is activated and pumps contaminants from the sealed spaced formed within the package.

**Patent Right  
Change**

Application number	085113617
Licensing	No
Mortgage	No
Transfer	Yes
Succession	No
Trust	No
Opposition	No
Invalidation	No
Cession	
Revocation	
Issue date of patent right	19990821
Patent grant date	20161106
Maintenance fee due	20090820
Years of maintenance paid	010